



Available From:

Approved
Fire Protection Co.

CALL FOR PRICING

Main Office
114 Saint Nicholas Avenue
South Plainfield, NJ 07080-1808
Phone: 908-755-2222
Fax: 908-769-1424

Systems Division
4219 South Clinton Avenue
South Plainfield, NJ 07080-1325
Phone: 908-226-5313
Fax: 908-226-5319

Visit us online at: www.afpnj.com

GasAlert MaxXT II

multi-gas detector



Go the distance, and save

GasAlertMax XT II is the smart, simple, economical way to compliance. Workers feel safe and incidents are minimized so everyone will be able to do more. That means savings realized from business continuity and productivity.

Simple operation, with SmartSample pump.

GasAlertMax XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorized pump for intelligent, remote sampling, ideal for confined spaces. The GasAlertMax XT II is fully compatible with MicroDock II automated test and calibration system.



H₂S
CO
O₂
LEL

WATER RESISTANT



- Minimize costs and training with one-button operation
- More accurate sampling results with SmartSample pump technology
- Compact, comfortable and field tough




BWF
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertMax XT II Specifications

Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm	
Weight	11.5 oz. / 328 g	
Temperature	-4 to 122°F / -20 to 50°C	
Humidity	10 - 100% RH (non-condensing)	
Alarms	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit), Low Battery, Pump	
Tests	Audible/visual alarms on activation, sensors, battery, pump and circuitry (continuous)	
Typical battery life	13 hours @ 32°F / 0°C 8 hours @ -4°F / -20°C Recharges in 6 hours	
Pump draw	Sample from up to 75 ft. / 23 m	
User options	Confidence beep	Force calibration when overdue
	Safety (sensor) lock	
	Latching alarms	Sensor configuration
	Safe display mode	Detector identification
	Calibration IR lock	Low alarm acknowledge
	Location selection	Language choices (five)
	Force block test	Set custom start-up message
	Force bump test when overdue	Confidence interval Datalog interval
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC	
Ingress Protection	IP66/67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D IECEX: Ga Ex ia IIC T4 ATEX: CE  II 1 G Ga Ex ia IIC T4  Br Ex ia IIC T4	
Warranty	Full two year warranty including all sensors	

Additional GasAlertMax XT II features:

- Integrated sampling pump with reliable diaphragm technology
- Best in class block detection with semi-conductor pressure sensor
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your detector with Fleet Manager II
- Equipped with standard datalogging and event logging

Options and Accessories



MicroDock II compatible



Belt holster



Multi-unit cradle charger



Concussion-proof boot

For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications

Gas	Measuring Range	Resolution
H₂S	0-200 ppm	1 ppm
CO	0-1000 ppm	1 ppm
O₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm setpoints for all sensors are user adjustable. Setpoint(s) are automatically displayed during instrument start-up.

Locally available from

Available From:



Main Office
114 Saint Nicholas Avenue
South Plainfield, NJ 07080-1808
Phone: 908-755-2222
Fax: 908-769-1424

Systems Division
4219 South Clinton Avenue
South Plainfield, NJ 07080-1325
Phone: 908-226-5313
Fax: 908-226-5319

Visit us online at: www.afpnj.com



Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: +1.403.248.9226
Toll free: 1.800.663.4164

www.gasmonitors.com

USA 1.888.749.8878
Europe +44 (0)1295.700.300
France +33 (0) 442.98.17.70
Germany 49 (0) 2137.17.6522

info@gasmonitors.com

Middle East +971.4.887.1766
S.E. Asia +65.6580.3468
China +86.10.6786.7305
Australia +61.3.9464.2770

Latin America +55.11.3475.1873
Other Countries +1.403.248.9226

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

6570-0-EN
© 2010 Honeywell International Ltd. All Rights Reserved.